

In the claims:

1. (currently amended) A power tool, in particular a handheld electric power tool, having a housing (10) with a coolant duct arrangement, having through openings (14), for a cooling medium for cooling at least one motor located in the housing (10), wherein the through openings (14) have a conical shape with respect to a longitudinal axis of the through openings, wherein the through openings (14) are located in a plate and each of said through openings has a cross-sectional area in the range from 0.15 mm² to 10 mm² measured in one plane with an outer surface of the housing (10) and of the plate, ~~wherein the through openings (14) are located in a plate,~~ wherein the plate is joined to the housing (10).

2. (original) The power tool according to claim 1, wherein the through openings (14) are provided at at least one coolant outlet.

3. (canceled)

4. (currently amended) The power tool according to claim 1, wherein the through openings (14) have a depth which is equivalent to at least one crosswise length of the through openings (14), wherein the at least one crosswise length corresponds to a cross section of the through openings (14) which lies in the one plane with ~~an~~the outer surface of the housing (10) and of the plate.

5. (previously presented) The power tool according to claim 1, wherein the through openings (14) are embodied as round.

6. (previously presented) The power tool according to claim 1, further comprising strut elements (20) arranged in a flow path inside the housing (10), wherein the elements (20) are provided with rounded edges and/or are encased in a casting composition (34).

7. (currently amended) A coolant duct arrangement having through openings (14) for a coolant, in particular for a power tool having a housing (10), wherein the through openings (14) have a conical shape with respect to a longitudinal axis of the through openings, wherein each of said through openings has a cross-sectional area in the range from 0.15 mm² to 10 mm² measured in the one plane with an outer surface of the housing (10).

8. (original) The coolant duct arrangement according to claim 7, wherein the through openings (14) have a perforation structure (18), with through openings (14) located in columns (24) and rows (26).

9. (currently amended) The coolant duct arrangement according to claim 7, wherein the through openings (14) have a depth which is equivalent to at least one crosswise length of the through openings (14), wherein the at least one crosswise

length corresponds to a cross section of the through openings (14) which lies in the one ~~place~~plane with an the outer surface of the housing (10) ~~and of the plate~~.

10. (currently amended) The coolant duct arrangement according to claim 7, wherein a rib width between two through openings (14) closest to one another measured in one plane with the outer surface of the housing is equivalent at most to one crosswise length of the through openings (14).

11. (previously presented) The coolant duct arrangement according to claim 7, wherein the through openings (14) are located in columns (24) and/or rows (26) of equal rib width.

12. (previously presented) The coolant duct arrangement according to claim 8, wherein the through openings (14) are combined in groups (28), which are spaced apart substantially equally in columns and/or in rows.

13. (previously presented) The coolant duct arrangement according to claim 12, wherein the through openings (14) within the groups (28) are separated from each other by different rib widths.

14. (canceled)

15. (currently amended) A coolant duct arrangement having through openings (14) with a conical shape for a coolant, in particular for a power tool having a housing, wherein the through openings (14) are located in a plate and each have cross-sectional areas in the range from $0.15 \text{ mm}^2 - 10 \text{ mm}^2$ measured in one plane with an outer surface of the housing (10) and of the plate~~and are located in a plate~~, wherein the plate is joined to the housing (10).

16. (previously presented) The coolant duct arrangement according to claim 7, wherein the through openings (14) are round.

17. (previously presented) The power tool according to claim 1, wherein the through openings (14, 14') are distributed over an entire face of the plate.

18. (currently amended) The coolant duct arrangement according to claim ~~46~~12, wherein the through openings (14) within the groups (28) have different diameters.